


[CONSUMER PRODUCTS HOME ▶](#)
[DOWNLOAD LIBRARY](#)
[SUPPORT](#)
[WHERE TO BUY](#)
[PROMOTIONS](#)
[CONTACT CANON](#)
[CAMERAS](#)
[CAMCORDERS](#)
[PRINTERS](#)
[SCANNERS](#)
[MULTIFUNCTION](#)
[COPIERS & FAX](#)
[BINOCULARS](#)
[NETWORK VIDEO SOLUTIONS](#)
[PROJECTORS & VISUALIZERS](#)
[CALCULATORS](#)
[SUPPLIES & ACCESSORIES](#)
[▶ SHOP](#)
[▶ CHOOSE THE RIGHT PRODUCT](#)
[▶ RESOURCES & LEARNING](#)
[▶ CANON ADVANTAGES](#)


Consumer Products Home :: Projectors & Visualizers :: LV-7585

LV-7585

Multimedia Projector

[✉ Email this Page](#)
[🔍 Find a Retail Store](#)

Item Code: 2473B002

Available in late-November 2007

[Overview](#)
[Features](#)
[Specifications](#)
[Supplies & Accessories](#)
[Support & Service](#)
[Drivers & Downloads](#)

Specifications

Specifications (Standard Configuration)

Item Code	2473B002AA
LCD Panel	1.3" TFT Poly-Silicon LCD X3 (with micro lens array)
Aspect Ratio	4:3
Native Resolution	(1024 x 768) XGA
Supported Resolutions	UXGA / SXGA+ / SXGA / WXGA / SVGA / VGA
Max Resolution	UXGA
Number of Pixels	786432
Brightness (ANSI Lumens)	6500
Uniformity	90%
Contrast Ratio	1600:1
Digital Keystone (Vertical)	+/- 40 Degree (Manual)
	+/- 20 Degree (Manual)

Optical Specifications

Projection Lens	F1.7 - 2.0, f=48.2 - 62.6 mm
Lens Shifting	Up/Down Ratio 1:1-10:0, Left/Right 2:3-3:2 Powered
Zoom	1.3x Powered
Focus	Powered

Screen Size	31" - 400" (Standard Lens)
Throw Distance	4.6-48.2ft. / 100":11.8-15.4 ft.
Throw Ratio	1.77-2.30:1 (Standard Lens)

Image Adjustments

Color Mode	Standard, High Contrast, Cinema. Custom
Color Adjust	RGB Manual
Mounting	Ceiling / Rear / Ceiling and Rear/ Upwards/ Downwards
Tilt Angle	Adjusting Feet up to 6.5 degrees

Input Signals

Scanning Frequency	H:15~100kHz, V:48~100kHz, Dot Clock 108MHz
Video Compatibility	1080i / 720p / 575p / 575i / 480p / 480i

Terminals

Inputs	DVI-D, D-sub 15, 5BNC, 3RCA, Mini-DIN 4 Pin
Outputs	D-sub 15
Built-in Speaker	No
Control Terminal	RS-232C (Dsub9)
Lamp	330W NSHA
Lamp Life	3000 / 2000 Hours (Normal / Quiet)

Remote Control

Wireless	Wireless Infrared
Mouse Control	Mouse Control Receiver (USB) w/ Drag and Drop

Ratings

Fan Noise	40/32 Bd
Power Consumption	490W / 392W
Power Voltage	AC 100 to 240V, 50/60Hz
Operating Temperature	41° to 95°F (5° to 35°C)
Storage Temperature	-14° to 104°F (-10° to 60°C), 20%RH ~ 80%RH
Dimension (WxHxD)	14.6 x 17.3 x 7.4 in. (not including lens)
Weight	28.7 lbs
Warranty	3 years parts and labor; 120 days lamp

Auto-Winding Filter System: up to 10,000 hours of usage before replacement.

[▲ Back to top](#)

Sign up to receive exclusive Canon savings & offers, new product announcements, product tips and much more!

Sign Up for RSS

RSS

© 2007 Canon U.S.A., Inc. All rights reserved. Duplication in whole or in part without permission is prohibited.

[Privacy Statement](#) :: [Terms of Use](#) :: [Site Map](#) :: [Online Security](#)